



DK005 Series

Top Side



Bottom Side



► Evaluation Carrier Board for 2I385PW / 2I847PW

► Features

- Flexible interface for verification
- Expedite customer's carrier board development
- LEX (150 x 200 mm) form factor
- Interface: 4 x mini PCIe, 2 x SIM holder, 1 x USB 3.0, 4 x USB 2.0, 9 x RJ45 (1 GbE + 8 x PoE), PWR / HDD / LAN LED, 4 x COM, 1 x VGA, 1 x HDMI, Line-out, Mic-in

Specification:

Model Name		DK005
Compatible SBC		2I385PW / 2I847PW
IO Connector	DVI / HDMI	1 x HDMI Type A
	VGA	1 (D-SUB)
	USB	1 x USB 3.0, 4 x USB 2.0
	Serial	4 x COM
	Ethernet	9 x RJ45 (1 x GbE + 8 x PoE)
	HD Audio	Line-out, Mic-in
	LED	Power, HDD
	DI / DO	MB Function
Expansion	Mini PCI Express	1 x (Full-size) PCIe / USB 1 x (Full-size) USB 2 x (Half-size) USB
	SIM card Holder	2
	80-pin Connector	2
	MircoSD card Holder	N/A
Dimension		200 x 150 mm
Power Input		Corresponding to M/B power DC-IN +9~36V
Operating Temp.		-20°C~70°C